



BTP



Environnement



Téléscopique



Chargeuse

Reinforced Body TP with central rib

BC.RTP

CHARACTERISTICS

- Width : from 2,00m to 3,00m
- Flat bottomed bucket
- Capacity : 500L to 5000L
- Blade of attack 250x30mm or 150x20mm following power machine
- High strength structure, outer axial strapping
- Shielding flat under and over the width of the bucket
- Full width cap
- Side cheeks with side reinforcements
- Kit of counterblade bolted 150x20 or 250x30
- Flat bottom



For carriers from
100 to 160 HP

OPTIONS

- Bolted or welded teeth
- Reinforced grapple special waste with longer teeth in 1 or 2 parts
- 330x30 reversible counterblade kit

Examples No exhaustive list	Width	Capacity Norme DOME	Capacity Norme DIN	Weight Excluding brackets
BC.RTP 24,5/20	2,45 m	2700 L	2250 L	1000kg
BC.RTP 24,5/25	2,45 m	3100 L	2600 L	1100kg
BC.RTP 26/25	2,60 m	2800 L	2400 L	1090kg
BC.RTP 28/30	2,80 m	3600 L	3 000 L	1300kg



LAMY "Les Constructeurs"
ZI NORD, F-28800 BONNEVAL
Tél. : + 33 (0)2 37 47 40 34
Fax : + 33 (0)2 37 96 21 91
www.lamy-les-constructeurs.com
exportsales@lamy-les-constructeurs.com

Your dealer :