



Environnement



Industrie



Télescopique



Chargeuse

Multifunctional body SPECIAL REINFORCED WASTE BMF.R.SDR Series

Series BMF.R.SDR

CHARACTERISTICS

- Very robust model adaptable on telescopic large capacity and loaders.
- Width : from 1,80m to 2,50m
- Box reinforcements across the single or double bucket depending on the power of the self-propelled.
- Blade of section 250mmx30mm 500HB (according to machine power)
- High quality grapple articulation system
- Shock absorbers
- Counterblade and cheeks

Types of grapples

- GRL.S.2E: grapple 20mm flat welded teeth with 2 blanks connecting the teeth to each other.
- GRL.S.2E.2P: Grapple in 2 parts welded teeth thickness 20mm with 2 blanks connecting the teeth between them.

OPTIONS

- Reinforced bolted counterblade
- Gripping cone on grapple



Grapple GRLS2E teeth overflowing

*For carriers from
100 to 250 HP*

Examples No exhaustive list	Width	Capacity	Weight Excluding brackets
BMF.R.SDR 23 / GRL.S.2E.22 (CLB+J)	2,30 m	1,60 m ³	930 kg
BMF.R.SDR 24,5 / GRL.S.2E.2P 24 (CLB+J)	2,45 m	1,70 m ³	1040 kg



LAMY "Les Constructeurs"
 ZI NORD, F-28800 BONNEVAL
 Tél. : + 33 (0)2 37 47 40 34
 Fax : + 33 (0)2 37 96 21 91
 www.lamy-les-constructeurs.com
 exportsales@lamy-les-constructeurs.com

Your dealer :