



Environnement



Industrie



Télescopique



Chargeuse

# Multifunction Bucket SPECIAL WASTE

## Series « BMF.SDR »

### CHARACTERISTICS

- Very robust model adaptable on telescopic large capacity and loaders
- Width: from 1.70m to 2.80m
- Flat bottom with central inner reinforcement and total belt under the bucket in connection with the hooking
- Inner central rib
- Bolted counter-blade + cheeks
- Shock absorbers



FOR CARRIERS FROM  
100 TO 250HP



GRL.S2E2P grapple with flush teeth

GRL.S2E grapple with overflowing teeth

Examples (No exhaustive list)	Width	Capacity DIN Standard	Weight Excluding brackets
<b>BMF.SDR (CLB+J) 23/GRL.S.2E.22</b>	2,30 m	1,50 m <sup>3</sup>	900 kg
<b>BMF.SDR (CLB+J) 24,5/GRL.S.2E.24</b>	2,45 m	1,60 m <sup>3</sup>	960 kg
<b>BMF.SDR (CLB+J) 27/GRL.S.2E.2P 26</b>	2,70 m	1,80 m <sup>3</sup>	1 120 kg



**LAMY "Les Constructeurs"**  
ZI NORD, F-28800 BONNEVAL  
Tél. : + 33 (0)2 37 47 40 34  
Fax : + 33 (0)2 37 96 21 91  
www.lamy-les-constructeurs.com  
exportsales@lamy-les-constructeurs.com

**Your dealer :**