



BTP



Environnement



Téléscopique



Chargeuse

Reinforced tipper

BR.TP

CHARACTERISTICS

- Width : from 2,00m to 2,60m
- Capacity : from 500L to 3300L
- Blade of attack 250x30mm or 150x20mm according to the power of the machine
- High strength structure, external strapping
- Shielding flat under and over the width of the bucket
- Side cheeks with side reinforcements
- Bolted counter blade kit (150x20 to 250x30)

OPTIONS

- Bolted or welded teeth
- Reinforced grapple special waste with longer teeth in 1 or 2 parts
- Reversible counter blade kit 330x30

*For carriers from
100 to 160 HP*



Examples No exhaustive list	Width	Capacity Din	Capacity Dôme 1/2	Weight Excluding brackets
BR.TP 23/15 Blade 150x20	2,30m	1430 L	1800 L	620kg
BR.TP 24.5/20 Blade 150x20	2,45m	2250 L	2700 L	1000kg
BR.TP 24.5/25 Blade 150x20	2,45m	2600 L	3100 L	1100kg



LAMY "Les Constructeurs"
ZI NORD, F-28800 BONNEVAL
Tél. : + 33 (0)2 37 47 40 34
Fax : + 33 (0)2 37 96 21 91
www.lamy-les-constructeurs.com
exportsales@lamy-les-constructeurs.com

Your dealer :